

LIVE100

MONOCOMANDO LAVATÓRIO PAREDE/BANCADA LIVERY





ASM TAPS®

WATER SOUL

EN WALL/DECK-MOUNTED CONCEALED
WASHBASIN MIXER LIVERY

FR MITIGEUR LAVABO ENCASTRÉE DE
MUR/PLAN LIVERY

ES MONOMANDO LAVABO EMPOTRAR DE
PARED/ ENCIMERA LIVERY



Rev.00

LIVE100





CARACTERÍSTICAS TÉCNICAS

PRESSÃO RECOMENDADA: RECOMMENDED PRESSURE:	3 - 4 BAR
TEMPERATURA RECOMENDADA: RECOMMENDED TEMPERATURE:	15°C - 65°C
MATERIAIS: MATERIALS:	Latão
TEMPERATURA MÁXIMA: MAXIMUM TEMPERATURE:	70°C
CAUDAL MÁXIMO A 3 BAR: MAXIMUM FLOW AT 3 BAR:	5L/MIN
LIGAÇÃO DE ENTRADA: INPUT CONNECTION:	G3/8"
LIGAÇÃO DE SAÍDA: OUTPUT CONNECTION:	G1/2"
PESO (KG): WEIGHT (KG):	1.95
DIMENSÕES EMBALAGEM (MM): SIZE PACKAGING (MM):	250x90x100


ACABAMENTOS

CR - CROMADO CHROME CHROME CROMO
PR - PRETO MATE BLACK MATT NOIR MAT NEGRO MATE
BR - BRANCO MATE WHITE MATT BLANC MAT BLANCO MATE
ST - SATINOX SATINOX SATINOX SATINOX
AT - ANTRACITE ANTHRACITE ANTHRACITE ANTRACITA
GM - GUNMETAL GUNMETAL GUNMETAL GUNMETAL
GMM - GUNMETAL MATE GUNMETAL MATT GUNMETAL MAT GUNMETAL MATE
OR - DOURADO GOLD DORÉ DORADO
ORM - DOURADO MATE GOLD MATT DORÉ MAT DORADO MATE
CB - COBRE COPPER CUIVRE COBRE
CBM - COBRE MAT COPPER MAT CUIVRE MAT COBRE MATE

TECNOLOGIA

-  AC540C - Cartucho Ø35 Energy Saving
AC540C - Ø35 Energy Saving Cartridge
-  Embutido a parede
Built-in to wall
-  Embutido ao balcão
Built-in to balcony
-  Abertura energia saving
Opening energy saving

! SERVICE



LIVE100

MONOCOMANDO LAVATÓRIO PAREDE/BANCADA LIVELY




A S M T A P S ®


W A T E R S O U L

INSTALLATION MANUAL


1 INSTALLATION




2 FIXED




3 CONNECTION



4 FIX IT



5 MAINTENANCE



6