

# LUX090B3

MONOCOMANDO DUCHE EMBUTIR  
CLIC 3 VIAS







ASM TAPS

WATER SOUL

EN *CONCEALED CLIC 3 WAY SHOWER  
MIXER LUX*

FR *MITIGEUR DOUCHE ENCASTRÉ CLIC 3  
VOIES LUX*

ES *MONOMANDO DUCHA EMPOTRAR CLIC 3  
VIAS LUX*



Rev.00

LUX090B3

## CARACTERÍSTICAS TÉCNICAS

PRESSÃO RECOMENDADA: RECOMMENDED PRESSURE:	3 - 4 BAR
TEMPERATURA RECOMENDADA: RECOMMENDED TEMPERATURE:	15°C - 65°C
MATERIAIS: MATERIALS:	Latão
TEMPERATURA MÁXIMA: MAXIMUM TEMPERATURE:	70°C
CAUDAL MÁXIMO A 3 BAR: MAXIMUM FLOW AT 3 BAR:	L/MIN
LIGAÇÃO DE ENTRADA: INPUT CONNECTION:	G1/2"
LIGAÇÃO DE SAÍDA: OUTPUT CONNECTION:	G1/2"
PESO (KG): WEIGHT (KG):	3,55
DIMENSÕES EMBALAGEM (MM): SIZE PACKAGING (MM):	285x200x170


## ACABAMENTOS

CR - CROMADO   CHROME   CHROME   CROMO
PR - PRETO MATE   BLACK MATT   NOIR MAT   NEGRO MATE
BR - BRANCO MATE   WHITE MATT   BLANC MAT   BLANCO MATE
ST - SATINOX   SATINOX   SATINOX   SATINOX
AT - ANTRACITE   ANTHRACITE   ANTHRACITE   ANTRACITA
GM - GUNMETAL   GUNMETAL   GUNMETAL   GUNMETAL
GMM - GUNMETAL MATE   GUNMETAL MATT   GUNMETAL MAT   GUNMETAL MATE
OR - DOURADO   GOLD   DORÉ   DORADO
ORM - DOURADO MATE   GOLD MATT   DORÉ MAT   DORADO MATE
CB - COBRE   COPPER   CUIVRE   COBRE
CBM - COBRE MAT   COPPER MAT   CUIVRE MAT   COBRE MATE

## TECNOLOGIA

	AC2140 - Válvula on/off FSG D6 control volume AC2140 - FSG D6 on/off clic valve
	AC540A - Cartucho Ø35 AC540A - Cartridge Ø35
	Embutido a parede Built-in to wall
*	.
*	.
*	.
*	.
*	.
*	.

# ! SERVICE



# LUX090B3

## MONOCOMANDO DUCHE EMBUTIR CLIC 3 VIAS




A S M T A P S


W A T E R S O U L

### INSTALLATION MANUAL


#### 1 CONECTION




#### 2 FIXED




#### 3 REMOVE PROTECTION



#### 4 FIX IT



#### 5 FIX IT



#### 6 MAINTENANCE

